

Amphenol Automotive

Amphenol-Tuchel Electronics GmbH



ABX-5® 90° without ferrite

CA 288T XXXX XXXX



PRODUCT CHARACTERISTICS

Features	- Pig tail supplied with different cable lengths - Single wire - Twisted wire - Jacketed cable
----------	---

Mating design	- Serviceable locking legs - Pre-positioned CPA - Electric CPA monitoring - One step or two step mating - 'scoop-proof', 'kojiri-safe' nozzle
---------------	---

Terminal system	- O-type contact system - One piece terminal design - Selective gold plated - Integrated CPA monitoring switch
-----------------	---

Termination technology	- Wire termination welded
------------------------	---------------------------

DESIGN CHARACTERISTICS

Housing material	PBT
Contact material	CuNiSi

PERFORMANCE CHARACTERISTICS

Pull out force	>135N
Insertion force	<50N
Temperature range	-40°C to +120°C
Dielectric resistance	1000V / DC

CONNECTOR

Catalogue Number	CA 288T XXXX XXXX
Interface	Ø 11mm ISO 19072-5
Available codings	W (pink), X (purple), Y (grey), Z (green)
Wire size	0.35mm ² / 0.5mm ²
Suitable retainer	C252 H35 X1X E2 (ABX-5®)